



## TECHNICAL DATA SHEET

### CONTRACT MATT

High obliterating matt emulsion for use on new plaster.

#### AVAILABILITY

**Colour range** Brilliant White & Magnolia.  
**Packaging** 10 litres.

#### PROPERTIES

**Drying time** Under normal drying conditions touch dry 2 hours, recoatable after 4 hours. Allow for adequate ventilation during the drying period.

**Finish** Matt.

**Composition** Pigment: Titanium Dioxide, coloured pigments and extenders.  
Binder: Vinyl acetate copolymer.  
Solvent: Water.

**Spreading rate** Up to 13m<sup>2</sup> per litre depending on surface texture and porosity.

**Wet film thickness** 77 micrometres at 13m<sup>2</sup> per litre.

**Dry film thickness** 18 micrometres at 13m<sup>2</sup> per litre.

**Volume solids** 24% White other colours will vary.

**Flash point** Not applicable.

**VOC content** EU limit value for this product (cat.A/a): 75 g/l (2007) / 30 g/l (2010)

This product contains max. 2 g/l VOC

**Limitations** For interior use only. Not suitable for areas subjected to heavy condensation. Do not apply when air or substrate temperatures are likely to fall below 8°C or when the relative humidity is above 80% during application or the drying period.

#### PREPARATION

**New surfaces** All surfaces must be sound, clean, suitably dry and free from anything that will interfere with the adhesion of the materials to be applied. Powdery, polished plaster or dense surfaces should be primed with Macpherson Universal Primer. Porous surfaces should be 'mist' coated with Macpherson Contract Matt thinned with up to 40% clean water.

**COATING SYSTEM** Apply two coats as required

**APPLICATION** Stir well before use. Apply by brush or roller. For airless spray (dilution may be required). For further information contact the Customer Relations Team.

**CLEANING** Return surplus material to container. Wash with clean water immediately after use.

For further details on any products in the Macpherson Trade Paints range please call the Customer Relations Team on **0870 241 6457** or visit the Macpherson website: [www.macphersontrade.co.uk](http://www.macphersontrade.co.uk)

Crown Paints, PO Box 37, Hollins Road, Darwen, Lancashire BB3 0BG. Tel. 01254 704951





#### HEALTH AND SAFETY

Please refer to the Safety, Health and Environmental Information on the container. Take special precautions during the surface preparation of pre 1960's painted surfaces as they may contain harmful lead. For further information contact our Customer Relations Team. When preparing all surfaces avoid the inhalation of dust and/or metal particles. Wear a suitable facemask. Material Safety Data Sheets for this and all other Crown Paints products are freely available from the place of purchase or the address below. Store in secure dry conditions inaccessible to children or animals. Containers should be kept closed during storage. Do not empty into drains, watercourses or access routes to septic tanks.

#### GENERAL INFORMATION

Apply all products in accordance with BS 6150: 2006 Code of practice for painting of buildings and BS 8000: Part 12: 1989 Code of practice for decorative wallcoverings and painting. Under normal and frost free conditions this product will remain usable for up to two years if stored correctly and unopened.

Every care is taken to ensure that all information provided on this Technical Data Sheet is accurate. Crown Paints are unable to guarantee results as it has no control over the conditions under which its products are applied. For help or more information contact the Customer Relations Team on 0870 241 6457. Before using this product please ensure you have the latest information.

The information is correct at date of issue May 2009.

For further details on any products in the Macpherson Trade Paints range please call the Customer Relations Team on **0870 241 6457** or visit the Macpherson website: [www.macphersontrade.co.uk](http://www.macphersontrade.co.uk)

Crown Paints, PO Box 37, Hollins Road, Darwen, Lancashire BB3 0BG. Tel. 01254 704951

