



## TECHNICAL DATA SHEET

### STAIN BLOCKING PRIMER

A solvent-borne stain blocking primer for interior and exterior use over dry plaster, cement and brickwork. Stain Blocking Primer offers good adhesion, good opacity and excellent stain blocking properties.

#### AVAILABILITY

**Colour range** Off White.  
**Packaging** 1, 2.5, 5 litres.

#### PROPERTIES

**Drying time** Under normal drying conditions touch dry in 4 hours, recoatable after 16 hours. Allow for adequate ventilation during the drying period.

**Finish** Matt.

**Composition** Pigment: Titanium Dioxide and extenders.  
Binder: Epoxy ester.  
Solvent: Dearomatised White Spirit.

**Spreading rate** Up to 14m<sup>2</sup> per litre depending on surface texture and porosity.

**Wet film thickness** 72 micrometres at 14m<sup>2</sup> per litre.

**Dry film thickness** 27 micrometres at 14m<sup>2</sup> per litre.

**Volume solids** 39%.

**Flash point** 40°C (closed cup).

**VOC content** EU limit value for this product (cat.A/g): 450 g/l (2007) / 350 g/l (2010)  
This product contains max. 349 g/l VOC.

**Limitations** Do not apply when air or substrate temperatures are likely to fall below 5°C or when the relative humidity is above 80% during application or the drying period.

#### PREPARATION

**New surfaces** All surfaces must be sound, clean, suitably dry and free from anything that will interfere with the adhesion of the materials to be applied. Powdery, polished plaster or dense surfaces should be primed with Macpherson Stain Blocking Primer.

#### Previously decorated surfaces

All surfaces must be sound, clean, suitably dry and free from anything that will interfere with the adhesion of the materials to be applied e.g. dirt, grease etc. Remove all loose, failing or suspect paint. Feather edges of sound paint. Remove all dust. Organic growth must be removed and the areas treated with Crown Trade Fungicidal Solution. Fill any fixing holes, cracks and shallow surface defects with Sandtex Trade Ready Mixed Filler. Patch prime bare and filled areas with Macpherson Stain Blocking Primer. Wash remaining sound paint with hot water and liquid detergent solution to remove any contaminants, frequently changing the water. Any glossy or eggshell surfaces should be wet abraded to provide a key. Rinse with clean water to remove all residues. Allow to dry. If after cleaning any areas still contaminated with substances likely to cause staining and/or bleeding, patch prime with one coat of Macpherson Stain Blocking Primer.

For further details on any products in the Macpherson Trade Paints range please call the Customer Relations Team on **0870 241 6457** or visit the Macpherson website: [www.macphersontrade.co.uk](http://www.macphersontrade.co.uk)

Crown Paints, PO Box 37, Hollins Road, Darwen, Lancashire BB3 0BG. Tel. 01254 704951





COATING SYSTEM	Apply one or two coats as required.
APPLICATION	Stir well before use. Apply by brush or roller.
CLEANING	Return surplus material to container. Clean with a proprietary cleaner immediately after use.

#### HEALTH AND SAFETY

Please refer to the Safety, Health and Environmental Information on the container. Take special precautions during the surface preparation of pre 1960's painted surfaces as they may contain harmful lead. For further information contact our Customer Relations Team. When preparing all surfaces avoid the inhalation of dust and/or metal particles. Wear a suitable facemask. Material Safety Data Sheets for this and all other Crown Paints products are freely available from the place of purchase or the address below. Store in secure dry conditions inaccessible to children or animals. Containers should be kept closed during storage. Do not empty into drains, watercourses or access routes to septic tanks.

#### GENERAL INFORMATION

Apply all products in accordance with BS 6150: 2006 Code of practice for painting of buildings and BS 8000: Part 12: 1989 Code of practice for decorative wallcoverings and painting. Under normal and frost free conditions this product will remain usable for up to two years if stored correctly and unopened.

Every care is taken to ensure that all information provided on this Technical Data Sheet is accurate. Crown Paints are unable to guarantee results as it has no control over the conditions under which its products are applied. For help or more information contact the Customer Relations Team on 0870 241 6457. Before using this product please ensure you have the latest information.

The information is correct at date of issue May 2009.

For further details on any products in the Macpherson Trade Paints range please call the Customer Relations Team on **0870 241 6457** or visit the Macpherson website: [www.macphersontrade.co.uk](http://www.macphersontrade.co.uk)

Crown Paints, PO Box 37, Hollins Road, Darwen, Lancashire BB3 0BG. Tel. 01254 704951

